



Guide to Cement Top Requirements for Intermediate and Production Casing

- The intermediate or production casing must be cemented full length.
- If less than 180 metres of surface casing has been run, the intermediate or production casing shall be cemented full length.
- If at least 180 metres of surface casing has been run, the intermediate or production casing shall be cemented to at least 100 metres (unless otherwise shown) above the zone indicated, and to at least 100 metres above any shallower zone found to contain oil or gas.

ZONE ABBREVIATIONS	
BE BELLOY	MD MIDDLE DEVONIAN
BI BOW ISLAND	MN MANNVILLE
BR BELLY RIVER	MR MILK RIVER
BY BLUESKY	PR PEACE RIVER
C CARDIUM	PS PASKAPOO
CO COLORADO	SP SLAVE POINT
DC DOE CREEK	SR SPIRIT RIVER
DJ DUNVEGAN	SU SULPHUR POINT
ED EDMONTON	TR TRIASSIC
FS FISH SCALES	UC UPPER CRETACEOUS
G GETHING	UD UPPER DEVONIAN
JU JURASSIC	V VIKING
KR KEG RIVER	W WABAMUN
M MISSISSIPPIAN	WS SECOND WHITE SPECKS

- The cement top requirements shall be approved by a Board representative.

- These requirements are subject to change and priority shall be given to requirements specified on the well license, or by a representative of the Board.

Copies may be obtained from EUB Information Services, 640 5th Avenue S.W., Calgary, Alberta, Canada T2P 2G4