Cenovus EnCAID approval #10440J Performance presentation

Claire Hong

Staff Production/Completion Engineer

Dubert Gutierrez

Sr. Reservoir Engineer

AER offices

Calgary

селс

February 2015



Advisory

This document contains forward-looking information prepared and submitted pursuant to the Alberta Energy Regulator's requirements and is not intended to be relied upon for the purpose of making investment decisions, including without limitation, to purchase, hold or sell any securities of Cenovus Energy Inc. Additional information regarding Cenovus Energy Inc. is available at <u>cenovus.com.</u>



Cenovus EnCAID* introduction and overview

This presentation was prepared in accordance with AER Directive 054 - Performance Presentations, Auditing, and Surveillance of In Situ Oil Sands Schemes

Subsurface Issues Related to Resource Evaluation and Recovery

Directive 054, Section 3.1.1

Surface Operations, Compliance, and Issues Not Related to Resource Evaluation and Recovery

Directive 054, Section 3.1.2

AER Dir 054 Section 3.1.1

Subsurface issues related to resource evaluation and recovery





Subsurface issues: Table of contents

- 1. Scheme background
- 2. Geology / geoscience
- 3. Drilling and completions
- 4. Instrumentation
- 5. Scheme performance
- 6. Future plans



Scheme background

Subsurface section 1

EnCAID Approval #10440J 2014 annual performance presentation





Background

 The EnCAID project is an enhanced recovery scheme which displaces natural gas with combustion gases that are the result of combustion of residual bitumen in gas cap







Project overview

- Combustion of residual bitumen in gas cap
- Allows for displacement and repressurization of gas zone
- 100% Cenovus Energy Inc.





Geological / geoscience

Subsurface section 2

EnCAID Approval #10440J 2014 annual performance presentation





Summary of reservoir properties

Depth	465 TVD
Thickness	5 m
Average Porosity	~36%
Average Gas Saturation	~50%
Average Water Saturation	~30%
Average Bitumen Saturation	~20%



Wabiskaw stratigraphic cross-section



Drilling and completion

Subsurface section 3

EnCAID Approval #10440J 2014 annual performance presentation





Well layout





Drilling and completion

- No new wells were drilled
- No recompletions
- No workovers

Requirements under subsection 3.1.1 3c – wellbore schematics are included in the Appendix



Instrumentation

Subsurface section 4

EnCAID Approval #10440J 2014 annual performance presentation





Instrumentation in wells

Observation Well: 102/05-10-73-6W4

- Equipped with 3 piezometers
- Equipped with 10 thermocouples

Observation Well: 100/6-10-73-6W4

- Equipped with 1 piezometer
- Equipped with 10 thermocouples

Requirements under subsection 3.1.1 5a – wellbore schematics 5c and 5d are included in the Appendix



Observation wells bitumen pressure





Scheme performance

Subsurface section 5

EnCAID Approval #10440J 2014 annual performance presentation





Radius of combustion front

- Exact radius unknown
 - No baseline seismic
 - Single observation well
- Simulated based on
 - 102/5-10 and 104/5-10
 - Actual daily air injection rates
- Combustion front
 - Simulation estimates 90-100m
 - Analytical model estimates radius 120-130m





Project performance history

Year	Activity
2006	June - Ignition and start-up
2007	Q1 – Nitrogen response at 00/14-9-73-6W4/00 Q2 – Nitrogen response at 00/2-16-73-6W4/00, 00/11-15-73-6W4/00, Shut-in 00/14-9-73-6W4/00
2008	May – Nitrogen response at 00/1-17-73-6W4/00
2009	Jan – Gas production shut-in due to 00/6-18-73-6W4/00 segregation repair Jun – Nitrogen response at 00/7-8-73-6W4/00 Oct – Injectivity decrease observed, bailed out 57% clay/gelatious crude, 23% carbonates, 20% iron compounds
2010	Q1– 00/5-10-73-6W4/00 injector solvent squeeze treatment 12 liter/m Q4 – Shut-in 00/1-17-73-6W4/00, 00/2-16-73-6W4/00, 00/11-15-73-6W4/00. Removal of 00/5-10-73-6W4/00 thermocouple string and perform pressure fall off tests
2011	Q1 - 00/5-10-73-6W4/00 injector solvent squeeze treatment ~145 liter/m, successfully removed near plugging issue Mar/Apr $-$ 00/11-15-73-6W4/00 flowed N ₂ 85%
2012	Jul – Startup of 00/6-7-76-6W4/00 Oct – Primrose sales volumes flowing to Caribou gas facility
2013	Feb - Startup of 00/6-6-73-6W4/00 Mar- Shut-in 00/7-8-73-6W4/00
2014	Dec – Startup 00/10-12-73-7W4/00





Production / injection summary

Production Operations

Operating For	Air Injected	Bulk Gas Recovered	Formation Gas Recovered
>7 years	~ 207 e ⁶ m ³	~ 143 e ⁶ m ³	~ 123 e ⁶ m ³

Approved Producers

UWI	Status	UWI	Status
00/06-05-073-06W4/0	Flowing ~ 32% N_2	00/02-16-073-06W4/0	Shut-in ~ 84% N_2
00/06-06-073-06W4/2	Flowing <1% N_2	00/01-17-073-06W4/0	Shut-in ~ 85% $\rm N_2$
00/06-07-073-06W4/2	Flowing $< 1\% N_2$	00/10-11-073-07W4/0	Shut-in <1% N_2
00/07-08-073-06W4/0	Shut-in ~ 92% N_2	00/10-12-073-07W4/0	Shut-in until Dec 19th, 2014
00/11-15-073-06W4/0	Shut-in ~ 82% N_2		



EnCAID estimated project life

Estimated EnCAID life +/- years

- >2 years
- Or until uneconomical to blend
 Dependent on N2 blending primarily
 - Remaining 5 EnCAID producers will eventually have increasing nitrogen content
 - Blend EnCAID produced volumes with production from North Primrose Plant
 - At North Primrose Plant, natural gas declines ~15%/year
 - TCPL specs has to be met with heat value of minimum 36MJ/m³
 - Blend ratio of EnCAID gas: North Primrose gas ~ 1:4.5



K3 pool production







History production





Voidage replacement ratio (VRR) - 2014

January and mid-July

- Steady air injection rates
- Minor downtime due to weather related events

Mid-July to late-September

- Reduce air injection experiment to understand the min air flux rate
- estimated air flux rate between 1.5 3.0 MMscf/D
- Air compressors have no turn down ability
 Late September to December
- Minor downtime due to weather
- Resume steady air injection rate



Voidage replacement ratio (VRR)

	Monthly VRR	Cumulative VRR	VRR Regulatory Approved Limits Min Monthly
January	1.92	1.45	0.90
February	1.92	1.45	0.90
March	1.92	1.46	0.90
April	1.92	1.47	0.90
Мау	1.92	1.47	0.90
June	1.92	1.48	0.90
July	1.92	1.48	0.90
August	1.92	1.48	0.90
September	1.92	1.48	0.90
October	1.92	1.48	0.90
November	1.92	1.48	0.90
December	1.92	1.49	0.90
2014 Average	1.92		



VRR performance

Injection to Production Ratio





VRR history





K3 pool pressure

Average Pool Pressure History for EnCAID Wabiskaw K-3



Dates since Shut-in & Start-up



102/05-10-073-06W4 – Temp history

- Well was approved as
 - Cemented & abandoned concept
 - Cement inside tubing ~ 300mKB
 - Monitoring downhole temperature real time
- Downhole schematic
 - Appendix slide #72





Observation well temperature





Observation well temperature

100/06-10-073-06W4 Observation well temperature





Composition of injected / produced fluids

- EnCAID does not currently sample air injected
- EnCAID captures gas samples for analysis on the schedule located to the right and monitors compositional changes for each well
- Cenovus samples selective wells on more frequent basis then required under Approval 10440J
 - Once to six times / annum, varies with lease accessibility

Location	Min Approval Sampling Frequency
00/6-10-73-6W4/2	Semi- annual
00/6-5-73-6W4/0	Semi- annual
00/6-6-73-6W4/2	Semi- annual
00/6-7-73-6W4/2	Semi- annual
00/7-8-73-6W4/0	Semi- annual
00/11-15-73-6W4/0	Semi- annual
00/2-16-73-6W4/0	Semi- annual
00/1-17-73-6W4/0	Semi- annual
00/10-11-73-7W4/0	Semi- annual
00/10-12-73-7W4/0	Semi- annual
00/6-18-73-6w4/0	Annual
00/10-36-72-7W4/2	Annual
00/11-17-73-6W4/0	Annual
00/14-9-73-6W4/0	Annual



Nitrogen response



35

Nitrogen response outside K3 pool

Nitrogen took more than 8 years to show sign of migration to K1 pool

- Prior to December 2014 $N_2 < 1\%$ on 6-18-73-6W4M
- Post December 2014 N₂~7% on 6-18-73-6W4M

Low lying structural zone along the north side of Section 18 & 17 creates a barrier to the rest of K1 pool.

Typically significantly thinner ~1m thick gas cap in section 18 & 17





Low-Lying zone
K-3 Pool Material Balance





Subsurface key learnings

- Maintaining continuous air injection is key to maintaining steady combustion front
- Nitrogen effects on produced gas must be monitored on an ongoing basis and forecasted for future impacts on plant operations and gas sales quality
- Recognize value of thermocouple data for predication and history matching simulations
- Generation of thermal conductive heating into the bitumen
- Provides a process for recovering gas that would otherwise not be recoverable due to GOB shut-in



Future plans

Subsurface section 6

EnCAID Approval #10440J 2014 annual performance presentation





Future plans

- No changes in overall recovery strategy are planned at this time
- Amendment for horizontal air injection well



AER Dir 54 Section 3.1.2

Surface operations, compliance and issues not related to resource evaluation and recovery





Surface operations: Table of contents

- 1. Facility overview / modifications
- 2. Measurement and reporting
- 3. Environmental issues
- 4. Compliance statement
- 5. Future plans



Facility overview / modifications

Surface section 1

EnCAID Approval #10440J 2014 annual performance presentation





Site Layout





Process flow schematic





Plant performance - 2014

January to July

- Steady air injections
- Some weather related reductions

July 16 to September 24, 2014

Reduced air injection rate

August to year end

Resumption of steady air injections

Facility is operating as expected



Gas usage





Gas usage

	2014 (e ³ m ³ /D)	2013 e ³ m ³ /D)
January	5.21	4.78
February	5.90	4.50
March	5.86	5.07
April	5.78	5.19
Мау	5.76	5.19
June	5.87	5.32
July	4.25	5.33
August	2.73	5.7
September	3.28	5.67
October	5.74	5.9
November	5.64	4.82
December	6.13	4.85



Green house gas emissions

	2014 Tonnes	2013 Tonnes
January	477	323
February	472	275
March	519	342
April	498	340
May	521	351
June	504	349
July	405	361
August	300	386
September	326	371
October	511	399
November	484	315
December	538	342



Surface gas migration

Year	Observations
2005	No development yet at EnCAID site, set base line
2006	LEL disappeared when went to "Methane elimination mode" which is standard practice for these tests
2007	LEL detection in "Full Gas Detection Mode" disappeared in "Methane Elimination Mode" suggesting "Swamp gas" Report noted clay cap over most of the sites could be trapping methane from organic peat decomposition
2008	Collected low pressure gas samples for analysis at 5-10 & 11-15. Most tests confirmed "biogenic gas
2009	SDS concluded that in their opinion it is a biogenic gas/swamp gas problem. Single Sample showed above 100% LEL came from wet, sloppy & drilling mud type of soil west of well center
2010	SDS opinion it is a biogenic gas/swamp gas problem. 2010 LEL readings less then 2009 LEL readings. No samples taken
2011	SDS opinion is that gas detected through field screening is swamp gas from the organic material beneath the well site. The gas sample collected contained insufficient hydrocarbons for carbon isotope analysis.
2012	No test undertaken
2013	SDS considered two samples to be inconclusive as soil around the well center were highly saturated & swampy. No sample was submitted for isotope analysis
2014	SDS considered it was a biogenic gas/swamp gas problem.



Surface facility key learnings

- Safe operation of production and injection wells
- Geographical location provides challenges for instrumentation operations utilizing solar panels
- Purity of injection gases plays key role in maintaining injectivity
- Uneconomical to operate in today's pricing environment





Measurement and reporting

Surface section 2

EnCAID Approval #10440J 2014 annual performance presentation





Measurement reporting





Environmental issues

Surface section 3

EnCAID Approval #10440J 2014 annual performance presentation





Environmental compliance

 No environmental noncompliance events occurred since the last performance review



Compliance statement

Surface section 4

EnCAID Approval #10440J 2014 annual performance presentation





Compliance confirmation

• No noncompliance events occurred since the last performance review



Future plans

Surface section 5

EnCAID Approval #10440J 2014 annual performance presentation





Future plans

- No major initiatives or plans that may require submission of an application are being contemplated at this time
- No changes to overall plant design or amendments are anticipated at this time
- Tie in high pressure piping from new horizontal air injector to existing facility



Appendix





Gas composition 00/1-17-73-6W4/0





Gas composition 00/2-16-73-6W4/0





Gas composition 00/6-5-73-6W4/0





Gas composition 00/6-6-73-6W4/0





Gas composition 00/6-7-73-6W4/0





Gas composition 00/7-8-73-6W4/0





Gas composition 00/11-15-73-6W4/0





Gas composition 00/10-11-73-7W4/0



селоуиз

Gas composition 00/10-12-73-7W4/0





Gas composition 00/14-9-73-6W4/0





Gas composition 00/6-18-73-6W4/0





102/5-10-073-06W4M DH schematic

Well Diagram for 102/5-10-73-6W4 Observation Well



cenovus

Feb 25, 2015 © 2015 Cenovus Energy Inc

72
100/05-10-073-06W4 wellbore schematic



селоуиз

Feb 25, 2015 © 2015 Cenovus Energy Inc

102/05-10-073-06W4 wellbore schematic

0 2.1.4MDING 4 4 4 4 112 0.017.73.0.52.0. 4 1.017.73.0.52.0. 112 0.017.73.0.52.0. 112 0.017.73.0.52.0. 112 0.017.73.0.52.0. 112 0.017.73.0.52.0. 112 0.017.73.0.52.0. 112 0.017.73.0.52.0. 112 0.017.73.0.52.0. 112 0.017.73.0.52.0. 112 0.017.73.0.52.0. 112 0.017.73.0.52.0. 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 114 0.015 1140	MD)	mKB TVD)	ype: VE Incl	RTICAL - ORIGINAL HOLE, 2012-11-26 4:29:57 PM Schematic - Actual	
0 2 1 2 1 2 1 2 1 2 1 2 1 3 0 1 3 0 1 3 0 1 1 0 1 1 0 1 1 0 1 1 0 1 1 0 1 1 0 1 1 0 1 1 0 1 1 0 1 1 0 1 1 0 1 1 1 0 1 1 1 0 1	0				
4 -	0				
4 1.1. CASING 174 205. 70. 1741 175 205. 70. 1741 176 205. 70. 1741 186 205. 714. 204. 206. 186 205. 714. 204. 206. 174. 204. 206. 174. 204. 206. 174. 204. 206. 174. 204. 206. 174. 204. 206. 174. 204. 206. 201. 37. 205. 205. 174. 204. 200. 206. 47. 206. 201. 37. 205. 205. 174. 204. 200. 206. 47. 204. 206. 47. 204. 206. 47. 204. 206. 201. 37. 205. 206. 47. 206. 47. 206. 47. 206. 47. 206. 47. 206. 47. 206. 47. 206. 47. 206. 47. 47. 206. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 206. 47. 47. 47. 47. 47. 47. 47. 47. 47. 47	4				
174 174 175 176 175 176 175 176 175 176 <td>4</td> <td></td> <td></td> <td>1-1, CASING</td>	4			1-1, CASING	
171 Control, A. 219.1. 118 174.2.0.4 118 205.7.174.6.97 118 205.7.174.6.97 118 205.7.174.6.97 205 205.7.174.6.97 205 205.7.174.6.97 206 205.7.174.6.97 207 205.7.1746.97 208 205.7.1746.97 208 205.7.1746.97 208 205.7.1746.97 208 205.7.1746.97 208 205.7.10610.64 209 205.7.10610.64 440 440 05 441 442 450 451 05 25.7.10610.65 451 05 25.7.10610.65 451 05 25.7.10610.65 452 451 25.7.10610.65 453 456 25.7.10610.65 454 25.7.10610.65 455 25.7.10610.65 451 25.7.10610.65 451 25.7.10610.65 451 25.6.1062.0.45	174	,		205.7, 0.1, 174.1 1-2, FLOAT	
118 118 114 110 <th 110<="" td="" th<=""><td>175</td><td></td><td></td><td>COLLAR, 219.1, 174.2, 0.4 1.3, CASING</td></th>	<td>175</td> <td></td> <td></td> <td>COLLAR, 219.1, 174.2, 0.4 1.3, CASING</td>	175			COLLAR, 219.1, 174.2, 0.4 1.3, CASING
118 540.00000000000000000000000000000000000	184		,	205.7, 174.6, 9.7	
306 306 0.5 2-2.1 LUBING, 37, 306, 62.0, 306, 4, 120 307 307 0.5 302, 62.0, 306, 4, 120 440 440 0.5 305, 62.0, 306, 4, 120 441 442 445 0.5 303, 730, 62.0, 306, 4, 130, 450, 307, 4, 130, 450, 450, 450, 450, 450, 450, 450, 45	185			1-4, 5005 SHOE, 219.1, 184.3, 0.3	
307 307 0.5	306	306	9.0	73.0,62.0,3.7, 302.8	
338 337 0.5	307	307	<u>6.0</u>	2-3, TUBING, 73.0, 62.0, 306.4, 1.0	
440 440 0.5 442 445 0.5 0.5	338	337	9.0		
442 442 0.5 0.5 2.4, TUBING, A, 445 445 0.5 0.5 2.4, TUBING, A, 450 450 0.6 0.5 73.0, 62.0, 307.4, 450 451 0.6 0.5 73.0, 62.0, 46.8, 451 0.6 0.6 73.0, 62.0, 46.8, 452 454 0.6 2.5, TUBING, 5.0, 45.15, 453 454 0.6 2.5, TUBING, 5.20, 45.15, 454 454 0.6 2.5, TUBING, 5.20, 45.42, 454 454 0.6 2.5, TUBING, 5.20, 45.42, 454 454 0.6 9.1, 5.20, 45.42, 454 454 0.6 9.1, 5.20, 45.42, 471 471 471 471 473 473 473 0.6 9.1, 5.20, 45.42, 473 473 0.6 9.6, 5.0, 45.42, 473 473 0.6 9.6, 5.0, 45.42, 473 473 0.6 9.6, 5.0, 45.42, 473 473 0.6 9.6, 5.0, 45.42, 473 473 0.6	440	440	9.0		
445 445 0.5 2.4, TUBING, A. 447 447 0.5 2.4, TUBING, A. 450 450 0.5 2.5, TUBING, A. 451 0.5 0.5 2.5, TUBING, A. 452 451 0.5 2.5, TUBING, A. 453 454 0.5 2.5, TUBING, A. 454 454 0.5 2.5, TUBING, A. 457 457 0.5 2.5, TUBING, A. 457 457 0.5 2.5, TUBING, A. 457 457 0.5 2.5, TUBING, A. 458 0.5 0.6 2.5, TUBING, A. 451 471 471 471 471 471 471 0.6 0.454.2, 9. 473 473 0.6 0.454.2, 9. 473 473 0.6 0.454.2, 9. 471 471 0.6 0.454.2, 9. 473 473 0.6 0.454.2, 9. 473 0.6 0.6 0.454.2, 9. 473 0.6 0.6 0.453.2, 9. 473	442	442	<u>9</u> 0		
447 447 0.6 2.4, TUBING, 62.0, 307.4, 139.4 450 450 0.6 0.6 73.0, 62.0, 307.4, 139.4 452 451 0.6 73.0, 62.0, 446.8, 477, 050, 451.6, 256, TUBING, 2.6, TUBING, 2.6, TUBING, 2.7, TUBING, 2.7, 062.0, 451.6, 2.7, 066 457 457 0.6	445	445	9.0		
450 450 0.6 2-5, TUBING, R. 452 451 0.6 2-5, TUBING, R. 454 454 0.6 2-5, TUBING, R. 457 457 0.6 2-6, TUBING, R. 457 457 0.6 2-6, TUBING, R. 457 457 0.6 2-7, TUBING, R. 463 463 0.6 2-7, TUBING, R. 463 0.6 2-7, TUBING, R. 2-7, TUBING, R. 464 464 0.6 2-7, TUBING, R. 471 471 0.6 2-6, TUBING, R. 473 473 0.6 2-6, TUBING, R. 530 530 0.7 9.6 2-6, TUBING, R. 530 530 0.7 9.6 2-6, TUBING, R. 530 530 0.7 2-9, TUBING, R. 2-9, TUBING, R. 531 530 570, 62.0, 453.0, 65.0, 453.0, 65.0, 453.0, 65.0, 453.0, 65.0, 453.0, 65.0, 4	447	447	9.0	2-4, TUBING, 73.0, 62.0, 307.4, 139.4	
452 451 0.6 2-5, TUBING, 2.0, 446.8, 4.7 457 457 0.6	450	450	0.6		
454 454 0.6 0.6 2.6, TUBING, 451.5, 273.0, 62.0, 451.5, 273.0, 62.0, 451.5, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 454.2, 273.0, 62.0, 453.2, 273.0, 62.0, 463.2, 273.0, 62.0, 472.8, 273.0, 62.0, 62.0, 472.8, 273.0, 62.0, 62.0, 472.8, 273.0, 62.0, 472.8, 473.0, 62.0, 472.8, 473.0, 62.0, 472.8, 473.0, 62.0, 473.0, 62.0, 472.8, 473.0, 62.0, 62.0, 472.8, 473.0, 62.	452	451	0.6	2-5, TUBING, 73.0, 62.0, 446.8, 4.7	
457 457 0.6	454	454	9.0	2-6, TUBING, 73.0, 62.0, 451.5, 2.7	
463 463 0.6 2.7, TUBING. 464 464 0.6 73.0, 62.0, 454.2, 471 471 0.6 73.0, 62.0, 454.2, 473 473 0.6 2.8, TUBING. 473 473 0.6 2.8, TUBING. 473 473 0.6 73.0, 62.0, 463.2, 478 478 0.6 73.0, 62.0, 463.2, 478 478 0.6 73.0, 62.0, 463.2, 530 530 0.7 2.9, TUBING, 530 530 0.7 5.9, 62.0, 472.8, 531 530 0.7 57.0, 62.0, 472.8, 532 532 0.8 0.7 57.0, 52.0, 472.8, 533 532 0.8 0.7 57.0, 52.0, 472.8,	457	457	9.0		
464 464 0.6 0.6 471 471 0.6 2.8, TUBING, 2.0, 463.2, 73.0, 62.0, 463.2, 96. 473 473 0.6 0.6 2.9, 1UBING, 2.0, 463.2, 96. 478 478 0.6 0.6 2.9, 1UBING, 2.0, 463.2, 96. 478 478 0.6 0.6 2.9, 1UBING, 2.0, 463.2, 96. 530 530 0.7 5.0, 62.0, 472.8, 57.0, 65.0, 472.8, 57.0, 55.0, 65.0, 472.8, 57.0, 55.0, 65.0, 472.8, 57.0, 55.0, 65.0, 472.8, 57.0, 55.	463	463	9.0	2-7, TUBING, 3:0, 62:0, 454:2, 9:1	
471 471 0.6 2.8. TUBING. 473 473 0.6 2.8. TUBING. 478 478 0.6 73.0.62.0.463.2. 478 478 0.6 9.6 73.0.62.0.463.2. 530 530 0.7 9.6 73.0.62.0.463.2. 530 530 0.7 57.0 2.9, TUBING. 530 530 0.7 57.0 57.0.472.8. 530 530 0.7 57.0 57.0.472.8. 531 532 0.8 57.0 57.0.62.0.472.8. 532 532 0.8 57.0 52.0.472.8.	464	464	0.6		
473 473 0.6 2-8, TUBING, 2.3, 52.0, 463.2, 96 478 478 0.6 73.0, 62.0, 463.2, 96 530 530 0.7 73.0, 62.0, 472.8, 57.0 530 530 0.7 2-9, TUBING, 57.0 530 530 0.7 2-9, TUBING, 57.0 530 530 0.7 2-10, FLOAT 531 532 0.8 57.0	471	471	0.6		
478 478 0.6 2.9, TUBING, 530 530 0.7 2.9, TUBING, 530 530 0.7 2.0, E2.0, 472.8, 57.0 57.0 57.0 57.0, 530 530 0.7 57.0, 531 530 0.7 57.0, 532 532 0.8 529.8, 0.2	473	473	9.0	2-8, TUBING, 73.0, 62.0, 463.2, 9.6	
530 530 0.7 2-9, TUBING, 57.0 530 530 0.7 73.0, 62.0, 472.8, 57.0 530 530 0.7 57.0 531 530 0.7 57.0 532 532 0.8 529.8, 0.2	478	478	9.0		
530 530 0.7 2.10. FLOAT 530 532 532 532 0.8	530	530	0.7	2-9, TUBING, 73.0, 62.0, 472.8, 57.0	
532 532 0.8	530	530	0.7	2-10, FLOAT SHOE, 73.0, 529.8, 0.2	
	532	532	0.8		

селоуиз

103/05-10-073-06W4 wellbore schematic



селоуиз

Feb 25, 2015 © 2015 Cenovus Energy Inc

75

QUESTIONS





Feb 25, 2015 © 2015 Cenovus Energy Inc